

1/27

FIG.1a




FIG.1b





FIG.2a







FIG.2b

2/27



10/526986

3/27




FIG. 5c




FIG. 5b




FIG. 5a

10/526986

4/27




FIG.6a




FIG.6b

5/27

10/526986




FIG.7a




FIG.7b

6/27

10/526986




FIG.8



10/526986

8/27




FIG.9b



10 / 526986

9/27




FIG. 10

10/526986

10/27




FIG.11a





FIG.11b

10/526986

11/27



10/526986

12/27




FIG.13

10/526986

13/27




FIG.14

14/27





FIG.15


15/27

10/526986



16/27

10/526986




**FIG. 17a** Adaptive pulse positioning between the fourth and fifth-driven pulses



17/27

10/526986



10/526986

18/27





FIG.18


10/526986

19/27



10/526986

20/27



21/27

10/526986




FIG.21 Sensorless Flux Switching Motor Control Circuit used in Load Tests

22/27

10/526986





FIG.22 (part i)

23/27

10/526986



Results at 1.0 Nm and 1.8 Nm operating from 240 V ac.  
 Constant output power is maintained between these two points.

FIG.22 (part ii)

24/27

10/526986




FIG.23 (part i) Results at 1.2 Nm and 1.93 Nm operating from 280 V dc (255 V ac)  
Constant output power of around 1860 W is maintained between these two points.



25/27

10/526986




FIG.23 (part ii)

10/526986

26/27




FIG.24

10/526986

27/27




FIG. 26




FIG. 25